

# PRODUCT DATA



## IAQ 3000™

Acrylic Latex Block Filler

### DESCRIPTION

Product No.: 8330 White

Fiberlock IAQ 3000 is a high quality interior and exterior block filler formulated to fill small imperfections and pinholes in masonry block and porous concrete before topcoating. This product contains mineral type fillers and fine silica aggregates which fill voids in masonry surfaces. This 100% acrylic block filler is easy to apply, alkali resistant and provides a uniform surface capable of receiving all types of finish coats. Fiberlock IAQ 3000 is not water sensitive after application and its flexibility and durability are the best available for a block filler, far superior to cementitious and PVA type formulations.

### SURFACE PREPARATION

Nibs and mortar joints should be 'bricked down' to remove all protrusions and mortar splatters. All dirt, grease, oil and other contaminants should be removed by brushing or solvent washing.

### PRODUCT APPLICATION

Fiberlock IAQ 3000 is supplied ready-to-use, but can be thinned sparingly with water for proper application consistency if necessary. Maximum block filling qualities are achieved with use of a roller (3/8" in nap or longer). Apply Fiberlock IAQ 3000 full bodied, vertically and cross hatched horizontally to remove all roller ridges and unevenness in the block filler. Brushing should be done with a short stubby brush, working the material well into any pinholes, pores and voids. Material should be applied in horizontal sections with the block mortar lines serving as a guide. Spray application is not recommended because the silica content is abrasive to spray equipment.

### PROPERTIES

- Color: White
- Percent Solids: 70.6% by weight  
56.1% by volume
- Weight per gallon @ 70°F: 12.5 lbs
- Flash Point: None
- Shelf Life: @ 70°F, 36 months minimum, (in original factory sealed containers)
- Coverage:  
200 ft<sup>2</sup>/gal - average (varies with porosity of block)
- Dry Time @ 70°F:  
Recoat: 2 hours
- Packaged: 5 gallon containers



FIBERLOCK TECHNOLOGIES, INC.

150 Dascomb Road  
Andover, MA 01810 U.S.A.  
Toll Free: (800) 342-3755  
Tel.: (978) 623-9987 Fax: (978) 475-6205  
www.fiberlock.com

# APPLICATION PROCEDURES FOR FIBERLOCK IAQ 3000™

## APPLICATION TOOLS

Apply Fiberlock IAQ 3000 with brush or roller. Spray application is not recommended because the silica content is abrasive to spray equipment.

## PRECAUTIONS

Stir thoroughly. Do not mix with any other coatings, solvents or colors in oil. Do not apply when air or surface temperature is below 50°F or when drying conditions are poor. Keep from freezing.

## CLEAN UP

Clean tools and drippings with warm soapy water before Fiberlock IAQ 3000 dries. Dispose of all waste according to all existing local, state and federal regulations.

**KEEP OUT OF REACH OF CHILDREN  
FOR PROFESSIONAL USE ONLY  
DO NOT TAKE INTERNALLY  
Keep from freezing. Close container after each use.**

HMIS HAZARD RATING							
Health	1	Flammability	0	Reactivity	0	Personal Protection	A
HAZARD INDEX 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe							
PERSONAL PROTECTION CODE: A = Safety Glasses							

### IMPORTANT:

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither Fiberlock Technologies, Inc., nor its agents shall be responsible for the use or results of use of this product or any injury, loss or damage, direct or consequential. We recommend that the prospective user determine the suitability of Fiberlock IAQ 3000 for each specific project and for the health and safety of personnel working in the area.