



# MATERIAL SAFETY DATA SHEET

## Sikadur 52 - Part B

### HMIS

HEALTH	3
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	D

### 1. Product And Company Identification

**Supplier**

Sika Corporation  
201 Polito Ave  
Lyndhurst, NJ 07071

Company Contact: EHS Department  
Telephone Number: 201-933-8800  
FAX Number: 201-933-9379  
Web Site: www.sikausa.com

**Manufacturer**

Sika Corporation  
201 Polito Ave  
Lyndhurst, NJ 07071

Company Contact: EHS Department  
Telephone Number: 201-933-8800  
FAX Number: 201-933-9379  
Web Site: www.sikausa.com

**Supplier Emergency Contacts & Phone Number**

CHEMTREC: 800-424-9300  
INTERNATIONAL: 703-527-3887

**Manufacturer Emergency Contacts & Phone Number**

CHEMTREC: 800-424-9300  
INTERNATIONAL: 703-527-3887

Issue Date: 07/07/2005

Product Name: Sikadur 52 - Part B  
CAS Number: Not Established  
Chemical Family: Amine  
MSDS Number: 3069  
Product Code: 0396140

### 2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
NONYL PHENOL	84852-15-3	
PROPRIETARY BLEND OF ALIPHATIC & CYCLOALIPHATIC AMINES	Trade Secret	

### 3. Hazards Identification

**Eye Hazards**

Causes eye irritation. Corrosive to living tissue.

**Skin Hazards**

Causes skin irritation. Corrosive to living tissue.

**Ingestion Hazards**

May be harmful if swallowed.

**Inhalation Hazards**

May cause nose, throat, and lung irritation. Moderate respiratory irritant.

# MATERIAL SAFETY DATA SHEET

## Sikadur 52 - Part B

### 4. First Aid Measures

#### Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

#### Skin

In case of contact, immediately flush skin with soap and plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

#### Ingestion

If swallowed, do not induce vomiting unless directed to do so by medical personnel.

#### Inhalation

Remove to fresh air. If not breathing, give artificial respiration.

### 5. Fire Fighting Measures

**Flash Point:** 205 °F

**Autoignition Point:** N/AV °F

#### Fire And Explosion Hazards

Exposure to heat builds up pressure in closed containers.

#### Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO2.

#### Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

### 6. Accidental Release Measures

Avoid release to the environment. Use appropriate Personal Protective Equipment (PPE). Contain spill and collect with absorbent material and transfer into suitable containers. Do not flush to sewer or allow to enter waterways. Ventilate enclosed area.

### 7. Handling And Storage

#### Handling And Storage Precautions

Keep out of reach of children. Keep containers tightly closed.

#### Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

### 8. Exposure Controls/Personal Protection

#### Engineering Controls

Use with adequate general and local exhaust ventilation. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

#### Eye/Face Protection

Faceshield over safety glasses or goggles.

#### Skin Protection

Avoid skin contact. Chemical-resistant gloves. Lab coat or other work clothing to prevent skin exposure. Launder before reuse.

#### Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace

# MATERIAL SAFETY DATA SHEET

## Sikadur 52 - Part B

### 8. Exposure Controls/Personal Protection - Continued

#### Respiratory Protection - Continued

conditions warrant a respirator's use.

#### Other/General Protection

Wash thoroughly after handling.

#### Ingredient(s) - Exposure Limits

NONYL PHENOL

ACGIH TLV: NOT ESTABLISHED

OSHA PEL: NOT ESTABLISHED

IARC: NO

NTP: NO

### 9. Physical And Chemical Properties

#### Appearance

Light yellow to amber liquid.

#### Odor

Amine Odor

**Chemical Type:** Mixture

**Physical State:** Liquid

**Melting Point:** N/AV °F

**Boiling Point:** N/AV °F

**Specific Gravity:** 0.86

**Percent Volatiles:** N/AV

**Packing Density:** 7.16 pounds/gallon

**Vapor Pressure:** N/AV

**Vapor Density:** >AIR

**pH Factor:** 11.5-12

**Solubility:** N/AV

**Evaporation Rate:** Slower than ether

### 10. Stability And Reactivity

**Stability:** Stable

**Hazardous Polymerization:** Will not occur

#### Conditions To Avoid (Stability)

None Known

#### Incompatible Materials

Strong oxidizing agents, acid and epoxy resins under uncontrolled conditions.

#### Hazardous Decomposition Products

CO, CO<sub>2</sub>, Oxides of Nitrogen

#### Conditions To Avoid (Polymerization)

None Known

### 11. Toxicological Information

#### Miscellaneous Toxicological Information

None Known

# MATERIAL SAFETY DATA SHEET

## Sikadur 52 - Part B

### 11. Toxicological Information - Continued

#### Conditions Aggravated By Exposure

None Known

### 12. Ecological Information

No Data Available...

### 13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

Waste generators must determine whether a discarded material is classified as a hazardous waste. USEPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

### 14. Transport Information

#### Proper Shipping Name

Corrosive Liquid, Basic, Organic, NOS (Aliphatic & Cycloaliphatic Amines)

#### Hazard Class

8 PGII

#### DOT Identification Number

UN3267

#### DOT Shipping Label

CORROSIVE

#### Additional Shipping Paper Description

Shall be marked as a marine pollutant when offered for transportation in bulk containers.

Shall be marked as a marine pollutant when offered for transportation in non-bulk containers aboard a vessel.

### 15. Regulatory Information

#### U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

#### SARA Hazard Classes

Acute Health Hazard

#### SARA Section 313 Notification

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

### 16. Other Information

#### HMIS Rating

Health: 3

Fire: 0

Reactivity: 0

PPE: D

#### Revision/Preparer Information

MSDS Preparer: EHS Department

MSDS Preparer Phone Number: 201-933-8800

This MSDS Supersedes A Previous MSDS Dated: 11/05/2003

# **MATERIAL SAFETY DATA SHEET**

## **Sikadur 52 - Part B**

### **Disclaimer**

The data in this Material Safety Data Sheet relates only to the specific material herein and does not relate to use in combination with any other material or in any process. The information set forth herein is based on technical data that Sika believes to be reliable as of the date hereof. Since conditions of use are outside our control, we make no warranties, express or implied and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

SIKA CORPORATION

Printed Using MSDS Generator™ 2000